Frankana®



Item no. 311/138
Manufacturer's no. 7181354

Gas Pressure Control System Caramatic DriveOne Gas Tank, for Gas Tanks with 90 ° Tank Plate

Information

Dimensions	20 x 10 x 9 cm
Pack size	26.7 x 15.9 x 12.2 cm
Net weight	1.18 kg
Gross weight	1.18 kg
Catalogue page	516

The Caramatic DriveOne and DriveTwo gas pressure control systems enable heating while driving by means of an integrated mechanical crash sensor that blocks the gas in the event of an accident with a delay of 3.5 g ± 0.5 g acting directly on the trigger element. For an average vehicle weight, this corresponds to an impact speed of approx. 15 to 20 km/h on a solid obstacle.

- Europe-wide use possible with country-specific high-pressure hose lines – Caramatic ConnectDrive (not included in delivery)
- Test device for leak testing of the liquid gas installation without dismantling the pressure regulating device
- Version with outlet connection RVS 10 / 8 is equipped as standard with a transition piece for connection to 8 mm pipes.
- Nominal flow: 1.5 kg/h.

Caramatic DriveOne

Safety gas pressure control system for the operation of one-cylinder systems in recreational vehicles while driving.

Consists of: low-pressure regulator with overpressure safety

Specifications

Connection	Komb.A x RVS 10
Alignment	horizontal
Operating pressure	30 mbar
Max. pressure: PS	16 bar
Type	DriveOne
Variant	For gas tanks with 90° tank plate

Frankana® Caravan und Freizeit GmbH – Südstraße 4 – 97258 Gollhofen – Germany
info@frankana.de

device S2SR (ÜDS), mechanical crash sensor and test device