



Item no. 311/215
Manufacturer's no. 7184302



Safety Gas Pressure Regulator System Caramatic SafeDrive Plus G.2 (FR/CH/BE)

GOK

Information

Pack size	30.7 x 26.4 x 16.9 cm
Net weight	3.5 kg
Gross weight	3.5 kg
Catalogue page	518

Automatic safety gas pressure switch system for operating two-cylinder systems in motorhomes and caravans while travelling, for direct connection to the gas cylinders.

Consists of: central and switchover regulator with mechanical crash sensor with new pendulum solution and manometer, hose lines and regulator brackets.

Advantages and features

- Gas supply while driving thanks to integrated mechanical crash sensor with new pendulum solution that shuts off the gas flow in the event of an accident.
- Faster and simpler activation and reset after response
- More precise operation and therefore fewer malfunctions due to incorrect response behaviour
- Activation possible without any problems, even if the leisure vehicle is on an incline
- Simple retrofitting, as the regulator does not need to be wall-mounted. Mounted directly on the gas cylinder.
- Little space required for installation in the gas cylinder box
- Gas cylinder can also remain permanently open while driving
- Increased safety, as the gas supply is interrupted directly at

Specifications

Connection	G.2 Shell-F x RVS 10/8
Operating pressure	30 mbar
Gas consumption	1,5 kg/h
Max. pressure: PS	16 bar

the gas cylinder in the event of an accident

- Automatic switchover to the gas cylinder on the reserve side as soon as the gas cylinder on the operating side is empty
- Cylinders can be changed without interrupting operation
- Gas check valve: prevents the gas from leaking when the cylinder is changed.
- Medium-pressure hose (rubber with textile insert; cold-resistant to -30 °C; hose dimensions 6.3 x 3.5 mm) G 3/8 LH-ÜM x G 3/8 LH-ÜM x 450 mm for connecting the two regulators
- Medium-pressure hose (rubber with textile insert; cold-resistant to -30 °C; hose dimensions 6.3 x 3.5 mm) G 1/4 LH-ÜM x RVS 10 x 450 mm for connecting the system to the vehicle's supply line
- Suitable for connecting the Caramatic SafeControl remote display
- RVS 10 / 8 outlet connection is equipped as standard with a transition piece for connection to 8 mm pipes
- Brackets for safe storage of the regulator on the wall, e.g. when changing the gas cylinder

Ideal for use in **France, Belgium** and **Switzerland**.