



Item no. 309/301

Manufacturer's no. TTC-SC32(A)+

Pipe Fan TTC-SC32(A)+ to Boost Heating and Cooling Capacity



Information

Dimensions	20.5x8.6 cm
Pack size	35.5x13.5x11 cm
Net weight	800 g
Gross weight	800 g

- **Versatile application possibilities:** Ideal for ventilation applications in RV HVAC systems, dryers, grow rooms, greenhouses and tents. Ensures the transport of fresh air for effective heating and cooling.
- **Intelligent speed control:** Equipped with manual control of 6 speed levels, automatic temperature control and timer function for user-friendly adjustment.
- **Automatic temperature control:** At temperatures of 20 °C and below, the fans automatically switch off. At temperatures between 20 °C and 45 °C, the fan speed dynamically adjusts to the ambient temperature. Above 45 °C, the fans operate at maximum speed for optimal performance.
- **Robust IP55 design:** Waterproof fan design, suitable for all environments to ensure reliable performance under various conditions.
- **Practical accessories:** Incl. two sturdy steel pipe clamps that securely connect the aluminium pipe to your fan or other duct openings.
- **Compatibility:** Suitable for pipes with a diameter of 60 mm, ideal for a variety of applications.
- **Incl. rectifier:** for reliable power supply and improved performance.

Specifications

Colour	black
Cable length	3 m
Nominal capacity	4.8 W
Nominal voltage	12 V
Nominal current	0.4 A