



Item no. 311/206
Manufacturer's no. 6203841



Regulator Hose Line Set

GOK

Information

Dimensions	1200 mm
Pack size	30x22x6.5 cm
Net weight	600 g
Gross weight	720 g
Catalogue page	524

For connection to gas cylinders, for fuelling gas barbecues with a gas cartridge connection.

- Medium-pressure regulator type M50-F/SBS, 2.0 bar, 2 kg/h with 35° outlet and integrated hose rupture protection EFV (SBS) with manual opening, locking the gas flow if the hose is damaged.
- Medium-pressure hose (rubber with textile insert, cold-resistant down to -30 °C, hose dimensions 6.3 x 3.5 mm) G 3/8 LH-ÜM x plug-in coupling SKU.
- Connecting piece with plug nipple STN for easy unplugging of the hose line on one side, AG 7/16-28 UNEF or AG 1-20 UNEF for connection to the gas device on the other.
- Thanks to a special mechanism, the plug-in is manipulation-safe – unlocking is only possible with the plug nipple STN.

Please note: at the gas unit, a low pressure regulator is required for gas cartridges with connection thread IG 7/16-28 UNEF in accordance with EN 417 or IG 1-20 UNEF.

Specifications

Connection	KLF x AG Gas cart.
Operating pressure	2 bar
Pressure	2 bar