




Item no. 311/145
Manufacturer's no. 7168408



High-Pressure Hose Line Caramatic ConnectBasic G.8 (EU-Shell), 450 mm

GOK

Information

Dimensions	450 mm
Pack size	28.8 x 16.4 x 3.9 cm
Net weight	243 g
Gross weight	260 g
Catalogue page	520

High-pressure hose line for versatile applications

The Caramatic ConnectBasic G.8 (EU-Shell) high-pressure hose line is the ideal solution for connection to all wall-mounted low pressure regulator and switchover systems such as Caramatic BasicOne, Caramatic ProTwo or Caramatic SwitchTwo with M20 x 1.5 inlet. Thanks to a country-specific connection, it offers maximum flexibility and safety for use in the **UK**.

Robust and durable materials

The hose is made of high-quality rubber with a sturdy textile insert, which not only ensures exceptional durability, but also guarantees excellent cold resistance down to -30 °C. This makes the Caramatic ConnectBasic G.8 perfect for use in cold environments and extreme conditions.

Dimensions: 6.3 x 3.5 mm

Cylinder connection x regulator connection

Important note on use

Please note that the hose line with a length of 750 mm may only be used for cylinder holders with a pull-out mecha-

Specifications

Connection	G.8 (EU-Shell) x M20 x 1.5 ÜM
Colour	orange
Max. pressure: PS	30 bar
Type	G.8 (EU-Shell)

nism. This ensures safe and proper handling.

The Caramatic ConnectBasic G.8 (EU-Shell) high-pressure hose line is the ideal choice for a safe, reliable and flexible gas supply. Thanks to its high-quality materials and country-specific connection, it fulfils the highest demands and offers a durable solution for various applications.

Country of destination: GB, gas type: butane