



Item no. 300/577
Manufacturer's no. GG20234

Water Filter Kalkguard Stainless Steel Limescale Absorber

goodguards®
 — EINFACH SAUBERES WASSER —

Information

Dimensions	20x5.1 cm
Pack size	24x6.5x5.5 cm
Net weight	570 g
Gross weight	570 g
Catalogue page	423

The Kalkguard stainless steel limescale absorber offers an innovative solution for water descaling, completely without salt. Thanks to food-safe malic acid in granulate form, it offers up to 94% limescale protection. This provides optimal protection for your pipes and water-bearing devices, significantly extending their service life.

The device is not only capable of preventing new limescale but also improves the taste of the water. The high-quality V4A stainless steel housing is reusable, making the Kalkguard a long-lasting investment. With an impressive service life of up to 6000 litres per filter cartridge, this limescale absorber is extremely efficient and cost-saving.

The Kalkguard stainless steel limescale absorber is easy to install, as both the water inlet and outlet are equipped with a 3/8" external thread. Another advantage is the screw thread mechanism, which makes filter replacement particularly straightforward. Operation is guaranteed at a minimum pressure of 0.8 bar up to a maximum pressure of 4 bar, which also allows use in combination with a submersible pump – all without significant pressure loss in the water pipe.

Count on durable protection and water descaling with the

Specifications

Connection	3/8"
Pressure	4 mbar
Colour	silver

Kalkguard stainless steel limescale absorber and enjoy the benefits of limescale-free water for your devices and pipes.

- Water descaling without salt (SGS-certified technology)
- Up to 94% limescale protection thanks to food-safe amino acids
- Protection of pipes and water-bearing devices from limescale and thus a significant extension of service life
- Already deposited limescale is first gradually softened, dissolved and then removed
- High-quality, reusable V4A stainless steel housing
- Exceptionally long service life of up to 6000 litres per filter cartridge
- No significant pressure loss in the water pipe
- Water inlet: 3/8" external thread
- Water outlet: 3/8" external thread
- Screw thread for filter replacement
- Minimum pressure 0.8 bar (also works in combination with submersible pump)
- Maximum pressure 4 bar