




Item no. 311/142
Manufacturer's no. 7168702



High-Pressure Hose Line Caramatic ConnectBasic G.2 (Shell-F), 750 mm

GOK

Information

Dimensions	750 mm
Pack size	30.7 x 23.3 x 4.6 cm
Net weight	330 g
Gross weight	350 g
Catalogue page	520

Discover the Caramatic ConnectBasic G.2 (Shell-F) high-pressure hose line – your reliable connection solution for all wall-mounted low pressure regulator and switchover systems. Ideally suited for Caramatic BasicOne, Caramatic ProTwo or Caramatic SwitchTwo with M20 x 1.5 inlet, this high-quality product guarantees a safe and efficient gas supply.

Ideal for France

The Caramatic ConnectBasic G.2 was specially developed for use in **France**. It has been equipped with a country-specific connection for this purpose. The maximum pressure (PS 20 bar) is also adapted to the requirements in France.

Robust materials and high cold resistance

Made from hard-wearing rubber with a textile insert, the hose line can withstand even extreme conditions. It remains flexible and functional at temperatures as low as -30 °C, making it ideal for a wide range of applications.

Dimensions: 6.6 x 4.0 mm

Cylinder connection x regulator connection

Important note on use

Please note that the hose line with a length of 750 mm may

Specifications

Connection	G.2 (Shell-F) x M20 x 1.5 ÜM
Colour	black
Max. pressure: PS	20 bar
Type	G.2 (Shell-F)

only be used for cylinder holders with a pull-out mechanism. This guarantees optimum performance and safety during use. The Caramatic ConnectBasic G.2 (Shell-F) high-pressure hose line offers you a reliable and versatile solution for connecting to your gas regulator and changeover systems. With its robust design and ability to withstand extreme temperatures, it is the ideal choice for you and your gas supply.