Frankana®

Item no. 311/178
Manufacturer's no. 7168713

MADE IN GERMANY

High-Pressure Hose Line Caramatic ConnectBasic G.2 (Shell-F), 750 mm

GOK

Information

Dimensions	750 mm
Pack size	30.2 x 18.9 x 4.1 cm
Net weight	360 g
Gross weight	360 g
Catalogue page	520

Specifications

Connection	G.2 (Shell-F) x M20 x 1.5 ÜM
Colour	orange
Max. pressure: PS	30 bar
Type	G.2 (Shell-F)

The Caramatic ConnectBasic G.2 (Shell-F) high-pressure hose line is the ideal solution for connecting to all wall-mounted low pressure regulator or switchover systems such as Caramatic BasicOne, Caramatic ProTwo and Caramatic SwitchTwo with M20 x 1.5 inlet. It has been specially designed for use in **Switzerland** and **Belgium** and is equipped with the appropriate country-specific connection.

Product features:

- **Versatile compatibility:** perfect for Caramatic BasicOne, Caramatic ProTwo and Caramatic SwitchTwo
- **Robust construction:** The hose is made of rubber with a hard-wearing textile insert.
- **Cold-resistant:** reliable performance down to temperatures of -30 °C
- **Cylinder connection x regulator connection:** optimum connection for a secure and tight connection
- **Specifications:** 6.3 x 3.5 mm

Please note: the hose line with a length of 750 mm may only be used for cylinder holders with a pull-out mechanism.

Areas of application:

The Caramatic ConnectBasic G.2 (Shell-F) is ideal for use in households and motorhomes, for example, where a safe and reliable gas supply is required.

Why Caramatic ConnectBasic G.2 (Shell-F)?

Opt for the Caramatic ConnectBasic G.2 (Shell-F) high-pressure hose line and benefit from high quality, reliable performance and versatility. Thanks to its cold-resistant properties and robust construction, this hose line is the perfect choice for your gas supply needs.