Frankana®



Item no. 311/162
Manufacturer's no. 7111333

Safety Gas Pressure Regulator System Caramatic DriveOne Set, vertical

Information

Dimensions	26.3 x 11.3 x 15.2 cm
Pack size	27 x 16 x 12 cm
Net weight	2 kg
Gross weight	2 kg
Catalogue page	517

Specifications

Connection	AG M20 x 1.5 x RVS 10/8
Alignment	vertical
Operating pressure	30 mbar
Max. pressure: PS	16 bar
Type	DriveOneSet V

Safety gas pressure control system for operating one-cylinder systems in caravans and motorhomes while driving.

Consists of:

- Low pressure regulator with excess pressure protection S2SR (ÜDS)
- Mechanical crash sensor with pendulum solution
- Test device and wall bracket
- Caramatic ConnectClean with angle bracket
- Caramatic ConnectDrive

Advantages and features: gas supply while driving thanks to integrated mechanical crash sensor with a pendulum solution, which shuts off the gas flow in the event of an accident with a deceleration of 3.5 g ± 0.5 g acting directly on the trigger element. This corresponds to an impact speed of approx. 15 to 20 km/h on a fixed obstacle with an average vehicle weight.

Please note: complies with the requirements of DGUV Regulation 110-010 (German Social Accident Insurance – previously DGUV Regulation 79) and is suitable for use in commercially used caravans and motor caravans!

Frankana® Caravan und Freizeit GmbH – Südstraße 4 – 97258 Gollhofen – Germany
info@frankana.de